

FORMULARIO No. 1
COTIZACIÓN POR MEDIO DEL SECOP II

La Estrella, Antioquia 26 abril de 2023

Señores
AGENCIA LOGÍSTICA DE LAS FUERZAS MILITARES REGIONAL ANTIOQUIA CHOCO
Ciudad.

REF: SIP- 007-032-2023


El suscrito ELBA MARIA PEÑA GOMEZ, obrando en nombre y representación de INSTRUMENTACIÓN Y SERVICIOS SAS, con Nit 830.505.910-7, de conformidad con lo establecido en los documentos: especificaciones técnicas del bien y/o servicio e informe técnico de contratación que integran la solicitud de cotización, adelantado por la Agencia Logística de las Fuerzas Militares Regional Antioquia Choco, para la ADQUISICIÓN EQUIPOS DE DATALOGGER, DESHUMIFICADORES, PURIFICADORES DE AIRE, LUXÓMETROS PARA MEDIR LAS CONDICIONES MEDIO AMBIENTALES PARA EL ARCHIVO CENTRAL DE LA SEDE REGIONAL ANTIOQUIA-CHOCO DE LA AGENCIA LOGÍSTICA DE LAS FUERZAS MILITARES.

Por medio de la presente, hago cotización, de acuerdo a los equipos que se solicitan ante la necesidad que tiene la entidad. El presupuesto para la presente vigencia será por valor total de **(\$6.930.000)** pesos colombianos, discriminados, así:

ITEM	TIPO DE EQUIPO	CANTIDAD	VALOR UNITARIO SIN IVA	VALOR UNITARIO CON IVA	VALOR PROMEDIO O TOTAL
1	DATALOGGER	1	\$ 869.416	\$ 165.189	\$ 1.034.605
2	LUXÓMETRO	1	\$ 1.378.074	\$ 261.834	\$ 1.639.908
3	DESHUMIFICADOR	1	\$ 2.438.090	\$ 463.237	\$ 2.901.327
4	PURIFICADOR DE AIRE	1	\$ 913.744	\$ 173.611	\$ 1.087.355
	TOTAL	TOTAL CON IVA: \$ 6.663.195			

Nota 1: La presente cotización incluye el transporte y todos los gastos adicionales en los que pueda incurrir el Contratista para efectuar la entrega del bien de conformidad con el lugar de entrega, y demás requerimientos del supervisor del contrato.

Se les informa a los interesados en presentar cotización que deben diligenciar el formulario No. 1 con los valores cotizados para cada ítem, adicional a eso anexar en el formulario información sobre la razón social de la empresa, el NIT, nombre y firma del representante legal, dirección, teléfono y dirección electrónica de la empresa. Se le informa que el presupuesto asignado para el presente proceso de la vigencia 2023 es de (\$6.930.000).



ELBA MARIA PEÑA

FIRMA Y POSTFIRMA REPRESENTANTE LEGAL DEL OFERENTE
INSTRUMENTACIÓN Y SERVICIOS SAS

NIT: 830.505.910-7

Dirección: Calle 151 No. 18ª – 34 / oficina 302



The Temperature & Humidity Datalogger is designed with a high accuracy Temperature & Humidity Sensor. This datalogger is provided with features of high accuracy, fast response and stability. It is widely used for monitoring and collecting data of environment temperature and humidity.



DT-172

TEMPERATURE AND HUMIDITY DATALOGGER

- | Memory for 32,000 readings (16000 temperature and 16,000 humidity readings)
- | LCD to show some logging information easily
- | Freely selectable measurement cycle from 1 sec. to 24h
- | Download collected data through PC's USB
- | Max / Min display
- | Alarm display if user-defined maximum/minimum values are exceeded
- | Analysis software used to view graph for logging data

DT-172

Temperature And Humidity Datalogger



Technical Specifications

Relative Humidity	Overall Range	0 to 100%
	Accuracy (0 to 20 and 80 to 100%)	±5.0%
	Accuracy (20 to 40 and 60 to 80%)	±3.5%
	Accuracy (40 to 60%)	±3.0%
Temperature	Overall Range	-40 to 70°C (-40 to 158°F)
	Accuracy (-40 to -10°C and +40 to +70°C)	±2°C
	Accuracy (-10 to +40°C)	±1°C
	Accuracy (-40 to 14 and 104 to 158°F)	±3.6°F
	Accuracy (+14 to 104°F)	±1.8°F
Resolution	0.1%RH, 0.1°C	
Memory	32700 values	
Measuring cycle	1s to 24h	
Analysis software	2000 / XP / Vista	

Accessories

Battery, Instruction Manual, PC Interface Cable, Software, Instrument Lock.



Contact :

CEM INSTRUMENTS (INDIA) PVT. LTD.

32A, Ganesh Chandra Avenue, 4th Floor, Kolkata-700013

Tel: 033-22151376, 22159759

Email: info@cem-instruments.in / info@cem-india.com

Web: www.cem-instruments.in / www.cem-india.com


CEM INSTRUMENTS HEADQUARTER & FACTORY

19th Building, 5th Region, Baiwangxin Industry Park,
Songbai Road, Baimang, Xili, Nanshan, Shenzhen,
China, 518108

Tel: +86-755-27353188, Fax: +86-755-27653699



Foot Candle/Lux Meter



Accurate light level measurements

Plus analog output for capturing readings to a recorder

Features:

- Accurately displays light level in terms of Fc or Lux over three ranges:
Fc (0-200, 0-2000 and 0-5000Fc) and
Lux (0-2000, 0-20000, 0-50000Lux)
- Resolution of 0.1Fc or 1Lux
with 5% accuracy
- Select fast (0.2 second) or slow
(0.4 seconds) response
- Monitor light levels using outputs;
1mV per count analog output for
capturing readings to a recorder
- Utilizes precision photo diode and color
correction filter; Cosine/color corrected
- Dimensions: 6.4 x 2.8 x 1.2" (163 x 70 x 30mm);
Weight: 7.8oz (220g)
- Complete with 9V battery and light sensor with 45" (1.1m)
cable and protective cover



Ordering Information:

401025.....Foot Candle/Lux Meter
401025-NIST401025 with NIST Certificate
409996.....Vinyl Pouch Carrying Case





	25.49 Pint - Energy Star	35.63 Pint - Energy Star	49.2 Pint - Energy Star	49.2 Pint - Energy Star with Pump
				
JHS Model #	D025B-25Pt	D025B-35Pt	D026B-50Pt	D026B-50Pt-P
Brand	JHS	JHS	JHS	JHS
Performance				
Energy Star	Yes	Yes	Yes	Yes
Capacity - Pints/24hrs	25.49	35.63	49.2	49.2
Integrated Energy Factor (IEF)	1.66	1.87	1.81	1.81
Airflow Rate (CFM) - High / Low	131 /101	131 /101	188 /151	188 /151
Bucket Capacity (Pints)	8.50	8.50	16.90	14.80
Refrigerant Type/Charge amount (Oz)	R410a/4.94	R410a/6.71	R410a/7.41	R410a/7.41
Sound Level High/Low (dBA)	≤53dB(A)	≤53dB(A)	≤53dB(A)	≤53dB(A)
Electrical				
Voltage	115	115	115	115
Amps	2.6	3.5	4.8	4.8
Watts	295	370	525	525
Plug Capacity	125V/15A	125V/15A	125V/15A	125V/15A
Plug Type / NEMA#	A / 5-15P	A / 5-15P	A / 5-15P	A / 5-15P
Min Power Cord Length (ft)	6.0	6.0	6.0	6.0
Exterior Appearance				
Color	White	White	White	White
Front Grill	Smooth Front	Smooth Front	Smooth Front	Smooth Front
Air Intake	Front	Front	Front	Front
Air Discharge	Top	Top	Top	Top
Features				
Electronic Control				
Control Panel Design	LED	LED	LED	LED
Digital Display	Yes	Yes	Yes	Yes
Adjustable Humidistat	Yes	Yes	Yes	Yes
Default Humidity Setting	Yes	Yes	Yes	Yes
Fan Speeds	3	3	3	3
Auto Restart	Yes	Yes	Yes	Yes
Bucket Full Indicator	Yes	Yes	Yes	Yes
Muteable bucket full alarm	No	No	No	No
Timer	24 Hour	24 Hour	24 Hour	24 Hour
Check Filter	Yes	Yes	Yes	Yes
Wifi/Connected	NO	NO	NO	NO
Filter Type	Permanent mesh	Permanent mesh	Permanent mesh	Permanent mesh
Filter Access	Slide-Out	Slide-Out	Slide-Out	Slide-Out
Garden Hose Drain Connect	Yes	Yes	Yes	Yes
Easy Roll Casters	Yes	Yes	Yes	Yes
Auto Defrost	Yes	Yes	Yes	Yes
Low-Temp Operation	Yes	Yes	Yes	Yes
Drain Pump	No	No	No	Yes
Pump drain hose included	No	No	No	Yes
Agency Approvals				
Performance Certification	AHAM	AHAM	AHAM	AHAM
Safety Approvals	CSA	CSA	CSA	CSA
Dimensions, Weight & Shipping				
Unit Dimensions (In)				
Height	19.70	19.70	24.40	24.40
Width	13.80	13.80	15.40	15.40
Depth	10.20	10.20	11.30	11.30
Carton Dimensions (In)				
Height	21.10	21.10	26.20	26.20
Width	15.60	15.60	16.60	16.60
Depth	12.40	12.40	13.10	13.10
Weight (lbs)				
Net	32 lbs.	34.2 lbs.	39.7 lbs.	40.8 lbs.
Ship	35.3 lbs	37.5 lbs.	43 lbs.	44.1 lbs.

ROWENTA PURE AIR



Filtrado hasta el 99,99% de alérgenos y partículas finas*

Respira tranquilo con Pure Air. El purificador de aire de Rowenta filtra hasta el 99,99% de los alérgenos y partículas finas*, para un aire limpio en tan solo 6 minutos gracias a un sistema de filtración de alto rendimiento que incluye un filtro Allergy+. Con sensores de contaminación integrados y luces indicadoras del nivel de calidad del aire, se adapta automáticamente al aire de su hogar para una máxima filtración de día o de noche.

Tecnología	
tipo de productos	Purificador de aire
tipo de tecnología	Filtración
Actuación	
humo	300 m3/hora
Número de velocidades	4
Nivel de sonido	43dB(A)
Potencia máxima	65W
Otras características	
Area efectiva	120m2
Número de filtros	3
Inteligencia	
Modo automatico	✓
Modo nocturno	✓
Indicador de calidad del aire	✓
Sensores	Partículas
Comodidad en uso	
Panel de control	electrónico
Temporizador	1-2-4-8 horas
Comienzo demorado	NO
Indicador de cambio de filtro	✓
Manejar	Integrado
Bloqueo infantil	✓
Nivel de sonido máx.	63dB(A)

